

Favorit Diesel SAE 15W-40 API CH-4/SJ



Packages:

20L, 60L, 208L

Meets the requirements and specifications:

SAE 15W-40

API CH-4/SJ

[EN] Favorit Diesel SAE 15W-40 API CH-4/SJ is a special high-quality mineral-based motor oil for highly loaded diesel engines of trucks, regular buses, etc. Provides reliable engine performance under extreme loads and excellent protection against wear and corrosion of parts. Thanks to a special additive package, it has a low pour point and provides an easy cold start. High washing and dispersing properties guarantee perfect cleanliness of engine parts and reliable lubrication.

[RU] Favorit Diesel SAE 15W-40 API CH-4/SJ всепогодное универсальное моторное масло на минеральной основе, предназначенное для высоконагруженных дизельных двигателей грузовых автомобилей, рейсовых автобусов и т.п. Обеспечивает надежность работы двигателя при экстремальных нагрузках и отличную защиту от износа и коррозии деталей. Высокие моющие и диспергирующие свойства гарантируют идеальную чистоту деталей двигателя и надёжное смазывание.

Precautions: Avoid getting oil on the exposed areas. Wear protective gloves. In case of contact with eyes and mouth, rinse immediately with water and non-necessity consult a doctor. To remove the skin with soap. Dispose of waste oil in the designated areas. Do not discharge into the channel still apply, soil and water. Keep away from fire!

Storage conditions: Store in a tightly closed container at a temperature between -30°C to +30°C in a dry protected from direct sunlight place, away from source of ignition.

The shelf life of the oil for 5 years from date of manufacture.

Product Characteristics:

Name of indicator	Test methods	Value
Kinematic viscosity mm ² /c at 40 °C	STB ISO 3104-2003	105,97
Kinematic viscosity mm ² /c at 100 °C	STB ISO 3104-2003	13,98
Viscosity index	STB 1797	133,55
Flash poin, °C	GOST 4333	230
Pour point, °C	GOST 20287	-27
TBN, g KOH/kg	GOST 11362	9,2
Density at 20°C, kg/m ³	GOST 3900	883

The data provided is based on standard laboratory tests and given only as a reference. The indicators can vary within the permissible range.

Приведённые данные основаны на стандартных тестах в лабораторных условиях и предоставляются только как справочные.

Показатели могут варьироваться в пределах допустимой нормы.